

## TYPE 88 NEOPRENE DIAPHRAGM SHEET

**COLOR:** BLACK

**FEATURES:** A SPECIAL NEOPRENE COMPOUND WITH A HEAVY WEIGHT WOVEN (14.5 Oz.) NYLON INSERT FOR MAXIMUM STRENGTH.

**EQUIPMENT:** CONTROL VALVES AND ALL EQUIPMENT APPLICATIONS WHERE A DIAPHRAGM MATERIAL IS REQUIRED.

**LIMITATIONS:** TEMPERATURES -20°F TO 180°F



**REMARKS:** FOR APPLICATIONS REQUIRING MORE FABRIC STRENGTH THAN NEOPRENE/NYLON

Hardness	60 Shore A +/-5
Tensile	1000 PSI
Elongation	500%
Finish	Smooth
Test Method	Mullen Burst Test Rating Over 1000psi with 1" Square Opening
High Strength	Tear Resistant, Meets ASTM D2000 Type BC

### Sizes:

Thickness	Widths	PART NUMBER:
1/16"	48"	SDS-06248-ND
3/32"	48"	SDS-09348-ND
1/8"	48"	SDS-12548-ND
3/16"	48"	SDS-18748-ND
1/4"	48"	SDS-25048-ND